



### **LEGRAND AUXILIARY CHANGEOVER SWITCH DX<sup>3</sup> - 6 A 250 V~ - CONTACT POSITION - 0.5 MODULE**

#### Caracteristici tehnice

Signalling auxiliaries prong busbar adapted

To fit on the Stanga-hand side of DX<sup>3</sup> and TX<sup>3</sup> devices

Maximum number of auxiliaries per device:

3 signalling auxiliaries or

2 signalling auxiliaries + 1 remote tripping auxiliary

Allow insertion of the supply busbar, top side

No tool required for joining together the auxiliary and the main device.

Auxiliary contact

6 A - 250 V~ (changeover switch)

For MCBs, RCBOs, RCCBs, isolating switches or remote trip isolating switches

Indicates the position of the contacts of its associated device.

Fault signalling contact

6 A - 250 V~ (changeover switch)

For MCBs, RCBOs, RCCBs, isolating switches or remote trip isolating switches

Indicates the position of the contacts of its associated device

Numar de module : 0.5

Caracteristici generale

Signalling, remote tripping auxiliaries and motorised controls DX<sup>3</sup>

Pret: 63,30 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/auxiliary-changeover-switch-dx3-6-a-250-v-contact-position-0-5-module-222809>