



LEGRAND AUXILIARY CONTACT PENTRU "ON/OFF" SIGNALLING - PENTRU VISTOP 63 TO 160 A

Caracteristici tehnice

Accessories

Auxiliary signalling contacts

IP 2X - 5 A - 250 V

To be fitted inside Vistop isolating switches

Additional contact NO + NC

To be fitted on main contact Cat.No 0 227 04 in order to obtain 2 NO + 2 NC

Connection : lug 2.58 mm²

Caracteristici generale

VistopTMisolating switches - 32 to 160 A

Safety switches for on-load circuit breaking by visible isolation of the contacts

Double break type load switching with self cleaning contacts by rapid make and break movements

Fixing on rail EN 60715 or screw fixing (only on rail for Vistop 63 A)

Padlockable handle in open position: 1 to 3 padlocks Cat.No 0 227 97

2 versions for mounting on faceplate:

Dreapta side handle, supplied with seal to maintain the IP protection for the enclosures (up to IP 55), screws, self adhesive drilling template, extension rod (30 to 170 mm) for creating an external angle

direct front handle or external (for Vistop 63 to 160 A)

Pret: 126,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/auxiliary-contact-pentru-on-off-signalling-pentru-vistop-63-to-160-a-222818>