



## **LEGRAND BREAK GLASS EMERGENCY BOX-2 POSITION-SURFACE MOUNTING- IP44-ROSU BOX CU LED**

### Caracteristici tehnice

Break glass emergency boxes

Polycarbonate, Class II - IK 07

Equipped with:

hinged glass door with locking option by key

3 cable entries for CG ISO 16/20 (by top or bottom as reversible product)

2 entries from back of product O20

2 side entries for mini-trunking 20 x 12.5 and 32 x 12.5

1 NC contact and 1 NO contact

Breaking capacity:

400 V~ / 4.5 A

230 V~ / 6 A

48 V DC / 1 A

24 V DC / 1.5 A

Montaj incastrat option with boxes O85

Dim.: 125 x 125 x 71 mm (surface-mounting) IP 44 - 125 x 125 x 33 mm (Montaj incastrat) IP 30

Red boxes can be used for fire applications and manipulated by fire fighters

Yellow boxes can be used for emergency applications and manipulated by employees

2-position boxes

Equipment:

1 mushroom head button for pressing

1 finishing accessory for simple action release (glass break) or double action (glass break followed by pressing on mushroom head)

2 long life 230 V~ LED indicators (green/red)

Red box with LED

Caracteristici generale

Safety boxes 125 series - for emergency applications  
Pret: 448,84 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/break-glass-emergency-box-2-position-surface-mounting-ip44-rosu-box-cu-led-223084>