



LEGRAND CLEMA SIR VIKING 3 - SPRING - 1 CONNECT - 4 WIRES - PITCH 6 - GRI

Caracteristici tehnice

Connecting

Grey for standard circuit, blue for neutral conductor, orange for circuit not broken by the master isolating device

1 connection - 4 wires - 2 entries/2 outlets

Built-in end cap

Colour : Grey

Nominal cross-section : 4 mm²

Capacity - Rigid wire : 0.5 to 6 mm²

Capacity – Flexible wire : 0.5 to 4 mm²

Flexible wire with ferrule : 0.5 to 4 mm²

Pitch : 6 mm

Caracteristici generale

Viking™ 3 terminal blocks with spring connection - for copper cables

Screwless connection system, stainless steel spring type

Used to make the electrical connection between 2 rigid copper wires, or flexible copper wires with or without ferrules

Direct tool-free insertion of a rigid wire or flexible wire with ferrule, up to 6 mm pitch

2 areas for automatic insertion bridging combs (upper level only for 2-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 10,81 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-sir-viking-3-spring-1-connect-4-wires-pitch-6-gri-224119>