



### **LEGRAND CLEMA SIR VIKING 3 - SPRING - DISCONNECT - PENTRU FUSE CARTRIDGE 5X20**

#### Caracteristici tehnice

Disconnect terminal blocks 1 connection - 2 wires

Opening by means of blade type lever, handle lever or mini lever (with tool)

For fuse cartridge 5 x 20 with handle lever

Colour : Grey

Nominal cross-section : 2.5 mm<sup>2</sup>

Capacity - Rigid wire : 0.5 to 2.5 mm<sup>2</sup>

Capacity – Flexible wire : 0.5 to 2.5 mm<sup>2</sup>

Flexible wire with ferrule : 0.5 to 2.5 mm<sup>2</sup>

Pitch : 6 mm

#### Caracteristici generale

Viking™ 3 terminal blocks with spring connection - for copper cables

Screwless connection system, stainless steel spring type

Used to make the electrical connection between 2 rigid copper wires, or flexible copper wires with or without ferrules

Direct tool-free insertion of a rigid wire or flexible wire with ferrule, up to 6 mm pitch

2 areas for automatic insertion bridging combs (upper level only for 2-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 17,38 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-sir-viking-3-spring-disconnect-pentru-fuse-cartridge-5x20-224125>