



LEGRAND CLEMA SIR VIKING 3 - SPRING - PENTRU CONDUCTOR - 1 CONNECT - 3 WIRES - PITCH 5

Caracteristici tehnice

For protection conductor

Metal base

Screwless fixing on rail

PEN from 10 mm²

1 connection - 3 wires - 1 entry/2 outlets

Colour : Green/yellow

Nominal cross-section : 4 mm²

Capacity - Rigid wire : 0.5 to 6 mm²

Capacity – Flexible wire : 0.5 to 4 mm²

Flexible wire with ferrule : 0.5 to 2.5 mm²

Pitch : 5 mm

Caracteristici generale

Viking™ 3 terminal blocks with spring connection - for copper cables

Screwless connection system, stainless steel spring type

Used to make the electrical connection between 2 rigid copper wires, or flexible copper wires with or without ferrules

Direct tool-free insertion of a rigid wire or flexible wire with ferrule, up to 6 mm pitch

2 areas for automatic insertion bridging combs (upper level only for 2-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 29,62 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-sir-viking-3-spring-pentru-conductor-1-connect-3-wires-pitch-5-224130>