



### **LEGRAND CLEMA SIR VIKING 3 -SCREW -PENTRU CONDUCTOR -1 CONNECT - PLASTIC BASE -PITCH 6**

#### Caracteristici tehnice

##### Connecting

Grey for standard circuit, blue for neutral conductor, orange for circuit not broken by the master isolating device, red for special circuits (safety, protected, etc), green for protection conductor class II equivalent assemblies

1 connection - 1 entry/1 outlet

Colour : Green

Nominal cross-section : 4 mm<sup>2</sup>

Capacity – Rigid wire : 0.25 to 6 mm<sup>2</sup>

Capacity – Flexible wire with or without ferrules : 0.25 to 4 mm<sup>2</sup>

Pitch : 6 mm

##### Caracteristici generale

Viking™ 3 terminal blocks with screw connection - for copper cables

Used to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires

2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 7,46 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/clema-sir-viking-3-screw-pentru-conductor-1-connect-plastic-base-pitch-6-224141>