





## <u>LEGRAND CLEMA SIR VIKING 3 -SCREW -PENTRU CONDUCTOR -1 CONNECTION - METAL BASE -PITCH 5</u>

Caracteristici tehnice

For protection conductor

Metal base

1 connection - 1 entry/1 outlet

Screwless fixing on rail up to 10 mm pitch and with screws for pitch 12 and 15 mm

PEN from 10 mm<sup>2</sup> Colour : Green/yellow

Nominal cross-section: 2.5 mm<sup>2</sup> Capacity – Rigid wire: 0.25 to 4 mm<sup>2</sup>

Capacity – Flexible wire with or without ferrules: 0.25 to 2.5 mm<sup>2</sup>

Pitch: 5 mm

Caracteristici generale

Viking<sup>TM</sup> 3 terminal blocks with screw connection - for copper cables

Used to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires

2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 12,12 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/clema-sir-viking-3-screw-pentru-conductor-1-connection-metal-base-pitch-5-224143