



LEGRAND CLEMA SIR VIKING 3 -SCREW -METAL BASE -3 CONNECT ON 3 LEVELS **-PITCH 5 -GRI**

Caracteristici tehnice

For sensors and actuators

For connecting sensors (Cat.No 0 371 51) or actuators (Cat.No 0 371 52), and their shared Tensiune de alimentare unit using equipotential bridging comb Cat.Nos 0 375 46/47

3 connections on 3 levels - for actuator

Green/yellow marking for the lower level

Metal base

Screwless fixing on rail

Rigid wire capacity: 2.5 mm² max. with equipotential bridging comb

Colour : Grey

Nominal cross-section : 2.5 mm²

Capacity – Rigid wire : 0.25 to 4 mm²

Capacity – Flexible wire with or without ferrules : 0.25 to 2.5 mm²

Pitch : 5 mm

Caracteristici generale

Viking™ 3 terminal blocks with screw connection - for copper cables

Used to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires

2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 44,01 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-sir-viking-3-screw-metal-base-3-connect-on-3-levels-pitch-5-gri-224149>