



LEGRAND CLEMA SIR VIKING3 -SPRING -DISCONNECT -FR CIRCUIT NOT BROKEN W HANDLE LEVER

Caracteristici tehnice

Disconnect terminal blocks 1 connection - 2 wires

Opening by means of blade type lever, handle lever or mini lever (with tool)

For circuit not broken with handle lever

Circuit not broken by the master isolating device

Colour : Orange

Nominal cross-section : 2.5 mm²

Capacity - Rigid wire : 0.5 to 2.5 mm²

Capacity – Flexible wire : 0.5 to 2.5 mm²

Flexible wire with ferrule : 0.5 to 2.5 mm²

Pitch : 6 mm

Caracteristici generale

Viking™ 3 terminal blocks with spring connection - for copper cables

Screwless connection system, stainless steel spring type

Used to make the electrical connection between 2 rigid copper wires, or flexible copper wires with or without ferrules

Direct tool-free insertion of a rigid wire or flexible wire with ferrule, up to 6 mm pitch

2 areas for automatic insertion bridging combs (upper level only for 2-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Pret: 14,99 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-sir-viking3-spring-disconnect-fr-circuit-not-broken-w-handle-lever-224153>