



LEGRAND COMMUNICATION ACCESSORY PENTRU KEOR LINE RT LINE INTERACTIVE UPS

Caracteristici tehnice

Communication accessory

Standard interface for internal network (cards)

Connected to the IP network and equipped with management software, the interface allows the protection of one or more devices, or remote systems

Ensures control and supervision of the UPS and shared equipment, sends alerts (e-mails or messages), and turns off/restarts computers

Caracteristici generale

DAKER DK PLUS - On-line double conversion UPS (rack/tower) - single phase and three phase VFI

The main parameters of the UPS, including the battery charge level and faults, are displayed on the LCD screen on the front panel

The integrated communication software not only controls the UPS and its switch-off if there is a malfunction, and enables the user to test the main functions remotely, communicate via SNMP/Internet/network adaptor and access the functions of the UPS via the Internet, but can also send the user an SMS if specific events occur

The internal extension connector enables a WEB/SNMP card or a relay interface to be installed which provides insulated contacts for applications on industrial control panels or remote alarm panels

If there is an electronic fault, overload, overheating or for scheduled maintenance operations, the automatic or manual (optional) bypass ensures continuity of the Tensiune de alimentare for critical loads. A bypass switch is available for maintenance

Pret: 3.027,70 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/communication-accessory-pentru-keor-line-rt-line-interactive-ups-224231>