



### **LEGRAND COMMUNICATION PATCH CORD CX<sup>3</sup> - LUNGIME 500 MM**

Caracteristici tehnice

Connection accessories

Communication patch cords

Allows data transmission between the different module of CX<sup>3</sup> energy supervision system

Can be used instead of communication rails or to create a link between two rows (individually connected with communication rails)

Lungime 500 mm (10 patch cords)

Caracteristici generale

CX<sup>3</sup> energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX<sup>3</sup> energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>), locally ("Stand alone" ) or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 447,83 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/communication-patch-cord-cx3-lungime-500-mm-224239>