



## **LEGRAND DECORATIVE FRAME URA ONE - PENTRU SURFACE MOUNTING - ALB**

Caracteristici tehnice

Accessories

Decorative frame for surface-mounting installation

White colour

Caracteristici generale

URA ONE - indoor self-contained emergency lighting luminaire LED

LED non-maintained and maintained units

Certified to IEC and EN 60598-2-22 standards

High Putere LEDs with optimized lighting distribution

Low Consum switching Tensiune de alimentare. Fully recyclable

Plug-in back with pre-cutted holes grid to ease installation and maintenance

Automatic terminals with high capacity: 2 x 2.5mm<sup>2</sup>. IP 42 - IK 07

Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours. Charge monitor with a green LED. Opal diffuser

Tensiune de alimentare: 230 V~ ± 10% - 50/60 Hz. Class II

Flat Montaj incastrat integration into ceiling and wall with Montaj incastrat frame Cat.Nos 6 616 50/51

Decorative frame to enhance surface-mounting aesthetic integration Cat.Nos 6 616 54/55

Pret: 23,71 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/decorative-frame-ura-one-pentru-surface-mounting-alb-225271>