



## **LEGRAND DULAP DISTRIBUTIE XL<sup>3</sup> 125 - 3 RANDURI - 54 MODULE - SURFACE MOUNTING**

### Caracteristici tehnice

Surface mounting distribution cabinets

Capacity 18 module per row

White RAL 9003

Fully reversible cabinet (base, door and faceplates)

Furnizat cu:

removable and pivoting chassis with rails fitted. Rails can be individually removed for easy cabling on site

removable cable entry plate (top and bottom)

removable faceplates (for each row)

IP 2X screw terminal blocks for neutral and earth

blanking plates (5 module, separable per module or 1/2 module) 1 sheet of self-adhesive labels for circuit identification (marking per module)

Spacing between rails 150 mm

Adjustable rail (2-position) for fitting modular equipment or DPX<sup>3</sup> 160 moulded case circuit breakers

Can be fitted with perforated plates and solid faceplates for mounting non-modular products (2, 3 to 4-row cabinets)

Doors to be ordered separately

Number of rows : 3

Numar de module : 54

Height : 600 mm

Width : 450 mm

Depth : 128 mm

### Caracteristici generale

Surface mounting cabinets XL<sup>3</sup> 125 - from 18 to 72 module

IP 40 - IK 09 with door

IP 30 - IK 08 without door

Class II

Self-extinguishing: resistance to incandescent wire 650 °C

Conform to IEC 60670-24

Allows to achieve assemblies conform to IEC 61439-3

Pret: 615,16 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/dulap-distributie-xl3-125-3-randuri-54-module-surface-mounting-225345>