



LEGRAND LAMPA DE EMERGENTA B65 - STANDARD MAINTAINED / NON MAINTAINED - 350 LM - 1H - LED

Caracteristici tehnice

Standard luminaires - Maintained/Non-maintained (M/NM)

Standard luminaires require normal lighting manual switching off in order to test emergency lighting

These Maintained luminaires can also operate in Non-maintained mode according to the wiring of normal lighting

350 lm - 1h (LEDs)

Caracteristici generale

B65 LED - weatherproof self-contained emergency lighting luminaire LED

Weatherproof LED maintained and non-maintained units

Certified to IEC and EN 60598-2-22 standards

High Putere LEDs. IP 65 - IK 07

Plug-in base to ease fixing, cabling and connection

Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours

Charge monitor with a green LED. Tensiune de alimentare: 230 V \pm 10% - 50/60 Hz. Class II

High-capacity screw terminals (2 x 2.5mm²)

3 flexible cable entries for O16, 20 and 25 mm tubes

Can be equipped with metallic protection grids Cat.Nos 0 626 90/92

Pret: 603,45 LEI (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/lampa-de-emergenta-b65-standard-maintained-non-maintained-350-lm-1h-led-225970>