



## **LEGRAND LAMPA DE EMERGENTA U21 - STANDARD MAINTAINED / NON MAINTAINED - 200 LM - 1H - LED**

### Caracteristici tehnice

Standard luminaires

Require normal lighting manual switching off in order to test emergency lighting

Maintained/Non-maintained (M/NM)

Can also operate in Non-maintained mode according to the wiring of normal lighting

200 lm - 1h (LEDs)

### Caracteristici generale

U21 LED - indoor self-contained emergency lighting luminaires LED

LED maintained and Non-maintained units

Certified to IEC and EN60598-2-22 standards

High Putere LEDs

IP 42 - IK 04. Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries

Recharge time: 24 hours. Charge monitor with a green LED

Tensiune de alimentare: 230 V~ ±10% - 50/60Hz - Class II

High capacity screw terminals (2 x 2.5 mm<sup>2</sup>)

To install a full IP 65 solution, add IP 65 weatherproof box Cat.No 6 616 16

Montaj incastat in dry partitions (ceiling and wall): add Montaj incastat frame Cat.No 6 617 20. Montaj

incastat in masonry (brick or concrete wall): add both Montaj incastat box Cat.No 0 617 21 and Montaj

incastat frame Cat.No 6 617 20

Can be equipped with metallic protection grids Cat.Nos 0 626 90/92

Pret: 316,80 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-de-emergenta-u21-standard-maintained-non-maintained-200-lm-1h-led-225973>