



LEGRAND LAMPA DE EMERGENTA URA ONE - STANDARD NON MAINTAINED - 1H **- 350 LM - LED**

Caracteristici tehnice

Standard luminaires

Require normal lighting manual switching off in order test emergency lighting

Non-maintained

350 lm - 1h (LEDs)

Caracteristici generale

URA ONE - indoor self-contained emergency lighting luminaire LED

LED non-maintained and maintained units

Certified to IEC and EN 60598-2-22 standards

High Putere LEDs with optimized lighting distribution

Low Consum switching Tensiune de alimentare. Fully recyclable

Plug-in back with pre-cutted holes grid to ease installation and maintenance

Automatic terminals with high capacity: 2 x 2.5mm². IP 42 - IK 07

Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours. Charge monitor with a green LED. Opal diffuser

Tensiune de alimentare: 230 V~ ± 10% - 50/60 Hz. Class II

Flat Montaj incastrat integration into ceiling and wall with Montaj incastrat frame Cat.Nos 6 616 50/51

Decorative frame to enhance surface-mounting aesthetic integration Cat.Nos 6 616 54/55

Pret: 273,57 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-de-emergenta-ura-one-standard-non-maintained-1h-350-lm-led-225997>