



## **LEGRAND FILTEROSU RECTIFIED POWER SUPPLY TRANSFORMATOR** **MONOFAZAT - PRIM 230-400 V / SEC 24 V= - 60 W**

Caracteristici tehnice

Single-phase Putere supplies

Consisting of:

a safety transformer with interference filtering

double operating terminals

filter capacitors

fused protection in the secondary

a green operating Tensiune present indicator

24 V=

230-400 V  $\pm$  15 V~ (primary) / 24 V= (secondary)

Output : 60 W

Current : 2.5 A

Terminal capacity Flexible cables Input : 6

Terminal capacity Flexible cables Output : 6

Caracteristici generale

Filtered rectified Putere supplies

High reliability Putere supplies without any pollution on electrical networks

Supplied with an insulated coupling bar for fast connection between the – and T terminals up to 15 A

Clip-on only up to 24 W, clip-on or screw fixing up to 120 W

Above 120 W: screw fixing

Conform to standards IEC and EN 61558-2-6, UL 60950 and CAN/CSA-C22.2 No 60 950.00

UL USA and Canada agreements up to 240 W

Products suitable for building equipment conforming to standards EN 61131-2, EN 60204 and EN 60439-1

Pret: 1.221,83 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/filteros-rectified-power-supply-transformator-monofazat->

