



**LEGRAND INTREERUPATOR DIFERENTIAL RCD DX<sup>3</sup>-ID - 4P 400 V~ NUL PE PARTEA  
DREAPTA - 63 A - 500 MA - TIP A**

Caracteristici tehnice

4-pole - 400 V~ - neutral on Dreapta-hand side

A type

Sensitivity : 500 mA

In : 63 A

Numar de module : 4

Caracteristici generale

RCCBs - DX<sup>3</sup>-ID - residual current circuit breakers 16 A to 100 A - AC, A, F and B types

Conform to IEC 61008 - 1, IEC 62423 (B type and F type)

Compatible with prong-type and fork type supply busbars

AC type : detect sinusoidal AC residual currents

A type : detect sinusoidal AC and pulsating DC residual currents

F type (High immunity) : detect AC and pulsating DC residual currents

Enhanced immunity to unwanted tripping in disturbed environments

Detection of high frequency fault currents

B type : detect sinusoidal AC, pulsating DC and smooth DC residual currents

Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries and motorised controls

Pret: 514,65 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intreerupator-diferential-rcd-dx3-id-4p-400-v-nul-pe-parte-a-dreapta-63-a-500-ma-tip-a-227965>