



**LEGRAND INTRERUPATOR GENERAL TIP USOL 1600 - S1 ELECTRONIC RELEASE -  
4P - ICU 50 KA (400 V~) - IN 1600 A**

Caracteristici tehnice

MCCBs electronic release S1 fixed version

Adjustment of  $I_r$ ,  $I_{sd}$

Instantaneous protection  $I_f = 20$  kA

Green indicator lamp

Connector for test unit

Dynamic selectivity

4P version: adjustment of neutral on front panel

Breaking capacity  $I_{cu}$  50 kA (400 V~)

4P

In : 1600 A

Caracteristici generale

DPX<sup>3</sup> 1600 - S1 electronic release MCCBs from 630 to 1600 A

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Can be used with residual current relays

Do not accept DPX<sup>3</sup> electronic interface for Modbus Cat.No 4 210 75

Supplied complete with:

connection plates for bars

insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL<sup>3</sup> cabinets and enclosures

Pret: 17.267,70 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-1600-s1-electronic-release-4p-icu-50-ka-400-v-in-1600-a-228108>