



**LEGRAND INTRERUPATOR GENERAL TIP USOL 1600 - S2 ELEC RELEASE +  
CENTRAL - 4P - ICU 50 KA (400 V~) - IN 1250 A**

Caracteristici tehnice

MCCBs electronic release S2 with energy metering central unit fixed version

Adjustment of  $I_r$ ,  $I_{sd}$ ,  $t_r$ ,  $t_{sd}$

Instantaneous protection  $I_f = 20 \text{ kA}$

Green indicator lamp

Connector for test unit

Logic and dynamic selectivity

Breaking capacity  $I_{cu} 50 \text{ kA (400 V~)}$

4P

In : 1250 A

Caracteristici generale

DPX<sup>3</sup> 1600 - S2 electronic release MCCBs from 630 to 1600 A

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Can be used with residual current relays

Supplied complete with:

connection plates for bars

insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL<sup>3</sup> cabinets and enclosures

Pret: 14.742,70 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-1600-s2-elec-release-central-4p-icu-50-ka-400-v-in-1250-a-228141>