



LEGRAND INTERRUPATOR GENERAL TIP USOL 1600 - S2 ELECTRONIC RELEASE - 3P - ICU 36 kA (400 V~) - IN 1250 A

Caracteristici tehnice

MCCBs electronic release S2 fixed version

Adjustment of I_r , I_{sd} , t_r , t_{sd}

Instantaneous protection $I_f = 20 \text{ kA}$

Green indicator lamp

Connector for test unit

Logic and dynamic selectivity

Breaking capacity $I_{cu} 36 \text{ kA (400 V~)}$

3P

In : 1250 A

Caracteristici generale

DPX³ 1600 - S2 electronic release MCCBs from 630 to 1600 A

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Can be used with residual current relays

Supplied complete with:

connection plates for bars

insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL³ cabinets and enclosures

Pret: 13.708,51 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interruptor-general-tip-usol-1600-s2-electronic-release-3p-icu-36-ka-400-v-in-1250-a-228159>