



## **LEGRAND INTRERUPATOR GENERAL TIP USOL 630 - S1 ELECTRONIC RELEASE - 4P - ICU 36 KA (400 V~) - IN 250 A**

Caracteristici tehnice

MCCBs electronic release S1 - fixed version

Adjustment of  $I_r$ ,  $I_{sd}$

Instantaneous protection  $I_f = 5 \text{ kA}$

Green indicator lamp

Connector for test unit

Dynamic selectivity

4P version: adjustment of neutral on front panel

Breaking capacity  $I_{cu} 36 \text{ kA (400 V~)}$

4P

In : 250 A

Caracteristici generale

DPX<sup>3</sup> 630 - S1 electronic release MCCBs from 250 to 630 A

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Can be used with earth leakage module or with residual current relays

Do not accept DPX<sup>3</sup> electronic interface for Modbus Cat.No 4 210 75

Supplied complete with:

fixing screws

connection plates for bars

insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL<sup>3</sup> cabinets and enclosures

Pret: 5.620,18 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-630-s1-electronic-release-4p->

