



LEGRAND INTRERUPATOR GENERAL TIP USOL ECHIPAT CU CONTOR + E.L.C.BS - INTRERUPATOR GENERAL TIP USOL 250 - ICU 50 KA - 4P - 100 A

Caracteristici tehnice

MCCBs with energy metering central unit and electronic earth leakage module - fixed version

Protection against overloads:

I_r adjustable from 0.4 to $1 \times I_n$

t_r adjustable from 3 to 15s

Protection against short circuits:

I_{sd} adjustable from 1.5 to $10 \times I_r$

t_{sd} adjustable from 0 to 0.5s

Equipped with earth leakage module with LCD screen

Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A

Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)

Integrated energy metering central unit with LCD screen; currents, Tensiune, frequency, Putere, energy and harmonics

Breaking capacity I_{cu} 50 kA (400 V~)

4P

I_n : 100 A

Caracteristici generale

DPX³ 250 electronic release - MCCBs from 40 to 250 A

Can be mounted on rail or on plate in XL³ cabinets and enclosures

MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable and with DPX³ 160 and 250 common auxiliaries and accessories

Conform to IEC 60947-2

Pret: 9.378,17 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-echipat-cu-contor-e-l-c-bs-intrerupator-general-tip-usol-250-icu-50-ka-4p-100-a-228580>