



## **LEGRAND INTRERUPATOR GENERAL TIP USOL MCCB - INTRERUPATOR GENERAL TIP USOL 160 - ICU 50 KA 400 V~ - 3P - 16 A**

Caracteristici tehnice

MCCBs - fixed version

Thermal adjustable from 0,8 to 1 In

Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)

Breaking capacity Icu 50 kA (400 V~)

3P

In : 16 A

Caracteristici generale

DPX<sup>3</sup> 160 thermal magnetic - MCCBs from 16 to 160 A

Can be mounted on rail or on plate in XL<sup>3</sup> cabinets and enclosures

MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Supplied with fixing screws cage terminals 70 mm<sup>2</sup> max. (flexible cable) or 95 mm<sup>2</sup> max. rigid cable with accessories

Can be fitted with DPX<sup>3</sup> 160 and 250 common auxiliaries and accessories

Conform to IEC 60947-2

Pret: 961,52 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol-mccb-intrerupator-general-tip-usol-160-icu-50-ka-400-v-3p-16-a-228633>