



**LEGRAND INTRERUPATOR GENERAL TIP USOL MCCB CU E.L.C.B.S -
INTRERUPATOR GENERAL TIP USOL 160 - ICU 16 KA 400 V~ - 4P - 40 A**

Caracteristici tehnice

MCCBs with electronic earth leakage module - fixed version

Thermal adjustable from 0,8 to 1 In

Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)

Equipped with earth leakage module with LCD screen

Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A

Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0 s)

Breaking capacity Icu 16 kA (400 V~)

4P

In : 40 A

Caracteristici generale

DPX³ 160 thermal magnetic - MCCBs from 16 to 160 A

Can be mounted on rail or on plate in XL³ cabinets and enclosures

MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Supplied with fixing screws cage terminals 70 mm² max. (flexible cable) or 95 mm² max. rigid cable with accessories

Can be fitted with DPX³ 160 and 250 common auxiliaries and accessories

Conform to IEC 60947-2

Pret: 2.728,99 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-mccb-cu-e-l-c-bs-intrerupator-general-tip-usol-160-icu-16-ka-400-v-4p-40-a-228676>