



## **LEGRAND INTRERUPATOR GENERAL TIP USOL MCCB CU E.L.C.BS - INTRERUPATOR GENERAL TIP USOL 250 - ICU 50 KA 400 V~ - 4P - 100 A**

### Caracteristici tehnice

MCCBs with electronic earth leakage module - fixed version

Thermal adjustable from 0,8 to 1 In

Magnetic adjustable from 5 to 10 In

Equipped with earth leakage module with LCD screen

Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A

Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)

Breaking capacity Icu 50 kA (400 V~)

4P

In : 100 A

### Caracteristici generale

DPX<sup>3</sup> 250 thermal magnetic - MCCBs from 100 to 250 A

Can be mounted on rail or on plate in XL<sup>3</sup> cabinets and enclosures

MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)

Can be fitted with cage terminals 120 mm<sup>2</sup> max. (flexible cable) or 150 mm<sup>2</sup> max. rigid cable and with DPX<sup>3</sup>

160 and 250 common auxiliaries and accessories

Conform to IEC 60947-2

Pret: 4.410,05 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-mccb-cu-e-l-c-bs-intrerupator-general-tip-usol-250-icu-50-ka-400-v-4p-100-a-228711>