



## **LEGRAND IP65 WEATHERPROOF BOX PENTRU U21 LED INUSA SELF-CONTAINED EMERGENCY LIGHTING LUMINAIRES**

Caracteristici tehnice

Accessories

IP 65 weatherproof box

Caracteristici generale

U21 LED - indoor self-contained emergency lighting luminaires LED

LED maintained and Non-maintained units

Certified to IEC and EN60598-2-22 standards

High Putere LEDs

IP 42 - IK 04. Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries

Recharge time: 24 hours. Charge monitor with a green LED

Tensiune de alimentare: 230 V~ ±10% - 50/60Hz - Class II

High capacity screw terminals (2 x 2.5 mm<sup>2</sup>)

To install a full IP 65 solution, add IP 65 weatherproof box Cat.No 6 616 16

Montaj incastrat in dry partitions (ceiling and wall): add Montaj incastrat frame Cat.No 6 617 20. Montaj incastrat in masonry (brick or concrete wall): add both Montaj incastrat box Cat.No 0 617 21 and Montaj incastrat frame Cat.No 6 617 20

Can be equipped with metallic protection grids Cat.Nos 0 626 90/92

Pret: 83,78 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ip65-weatherproof-box-pentru-u21-led-inusa-self-contained-emergency-lighting-luminaires-229183>