



LEGRAND LIGHTING MANAGEMENT-DIGITAL PASSAGE DETECTION-CEILING MOUNTING-IR-360°-47 M

Caracteristici tehnice

Ideal for passage areas

PIR ceiling-mounting Lighting Management sensors, 360°

Fix directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm,
Cat.No 0 893 58

3-wire with neutral

Standby Consum: 0.4 W

Recommended fixing height: 2.5 m

Range 08 m

Optimum distance between 2 sensors: 6 m

Connection via automatic terminals

Surface mounted on ceiling using accessory Cat.No 0 488 75

Caracteristici generale

Lighting Management sensors for 1 circuit - Lighting Management sensors for passage areas with natural light

Check presence and natural light level continuously, switch off when there is sufficient natural light

Occupancy mode (automatic switch-on/off factory setting)

Can be used with push-button Cat.No 0 770 40 (or illuminated push-button Cat.No 0 770 33) for vacancy mode (manual switch-on and manual or automatic switch-off)

Precise on-site adjustment using configuration tool Cat.No 0 882 30

Adjustable time delay: 5 s to 59 min

Light level threshold adjustable from 5 to 1275 lux

Pret: 390,85 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lighting-management-digital-passage-detection-ceiling-mounting-ir-3600-47-m-229746>