



## **LEGRAND MODUL DE MASURA CX<sup>3</sup> - CONNECTION CU CT - 5 A - 1 MODULE**

Caracteristici tehnice

Measurement module

For measuring current, Tensiune, active/reactive Putere and other values

Conform to IEC/EN 61557-12

Accuracy: class 0.5

Connection with CT

5 A measuring module connected via current transformers (CT)

Consum: 0.391 W - 32.6 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX<sup>3</sup> energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX<sup>3</sup> energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>), locally ("Stand alone" ) or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 851,16 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-de-masura-cx3-connection-cu-ct-5-a-1-module-230599>