



## **LEGRAND SENZOR DE MISCARE VALENA LIFE - 250 W- IP44 - CU CAPAC - ALB**

### Caracteristici tehnice

Motion sensor without neutral 250 W IP 44

Compatible with any type of lamp

Detection field 120°

Detection range 8 m

Integrated self-protection against overloads and short-circuits

Screw terminals

Accepted Putere by lamp type:

LEDs 3 W to 100 W (if several sensors are installed on the same circuit, the minimum load increases)

compact fluorescent 3 W to 100 W (if several sensors are installed on the same circuit, the minimum load increases)

LEDs, CFLs, Halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 VA to 250 VA

230 V halogen, incandescent: 3 W to 250 W

Up to 3 sensors can be connected in parallel

Time delay setting from 10 s to 10 min.

Light level threshold setting from 5 lux to 1275 lux.

Standby Consum: 0.02 W

White

### Caracteristici generale

Valena™ Life - IP44 devices with white cover plate

Valena In'Matic mechanisms supplied with white cover plates, weatherproof membrane and support frames

To be equipped with plates

Supplied with mounted dust protection transparent shield

Flowpack packaging: robust protection to ensure optimum operation

Pret: 477,92 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/senzor-de-miscare-valena-life-250-w-ip44-cu-capac-alb->

