



LEGRAND ON-LINE DOUBLE CONVERSION UPS - 3000 VA - 2400 W- BACKUP TIME **10 MIN**

Caracteristici tehnice

UPS

The stated backup time in minutes is estimated and may vary according to the load characteristics, operating conditions and environment

Nominal Putere: : 3000 VA

Active Putere: : 2400 W

Backup time: : 10 min

Weight: : 53 kg

Caracteristici generale

Keor S - On-line double conversion UPS (tower) - single phase

For industrial environment (food industry, laboratories ...) or applications requiring long backup time (electro-medical ...)

Installation: downstream Putere generators. Possibility to add batteries for extended autonomy. Parallel connection possible: up to 4 UPSs. Advanced management depending on the battery discharge level

Sinusoidal output

LCD screen

Self-diagnosis

Putere factor: 0.9

Integrated automatic bypass and maintenance bypass. Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately

Cold Start Function. Microprocessor control

Telephone line/Internet (RJ 11/RJ 45)

Remote emergency shutdown function ("Emergency Putere Off" - EPO). Equipped with 4 wheels for easy moving of the UPS

Pret: 13.228,37 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/on-line-double-conversion-ups-3000-va-2400-w-backup-time-10-min-230969>