



**LEGRAND PANOU MONTAJ PRIZA PRISINTER HYPRA - IP44 - 380/415 V~ -16 A -
3P+N+E - METAL**

Caracteristici tehnice

LV prisinters

Dust resistance IP may be increased by rubber push-button (on request) - IP 55 cover closed or connected - IP 44 connected

380 to 415 V~ 50/60 Hz - 16 A 3P+N+E

To be associated with surface-mounting box Cat. No 0 522 49 for surface-mounting socket

Panel mounting socket - metal

16 A

Caracteristici generale

Hypra IP 44 sockets and plugs metal, plastic, rubber, IP 44/55 Prisinter - LV 16 to 63 A and ELV 16 and 32 A

Conform to IEC 60309-1 and IEC 60309-2

IP 44 according to IEC 60529

IK 09: plastic and rubber

IK 10: metal according to IEC 62262

Self-extinguishing:

850°C (support of active parts) / 960 °C for Prisinter)

650 °C: plastic housing conform to IEC 60695-2-10

50°C to + 100°C (- 20°C for Prisinter)

Pret: 1.492,41 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/panou-montaj-priza-prisinter-hypra-ip44-380-415-v-16-a-3p-n-e-metal-231315>