



## **LEGRAND PANOUL MONTAJ PRIZA-INCLINATA HYBRA-IP44 -380/415 V -16 A -3P+N+E** **-PLASTIC**

### Caracteristici tehnice

LV panel mounting sockets

380 to 415 V~ 50/60 Hz - 16 A 3P+N+E

To be associated with box Cat.No 0 522 29 for surface-mounting socket or Cat.No 0 522 89 for through wiring surface mounting socket

Plastic

Pack = 5

16 A

### Caracteristici generale

Hypra IP 44 sockets and plugs metal, plastic, rubber, IP 44/55 Prinsinter - LV 16 to 63 A and ELV 16 and 32 A

Conform to IEC 60309-1 and IEC 60309-2

IP 44 according to IEC 60529

IK 09: plastic and rubber

IK 10: metal according to IEC 62262

Self-extinguishing:

850°C (support of active parts) / 960 °C for Prinsinter)

650 °C: plastic housing conform to IEC 60695-2-10

50°C to + 100°C (- 20°C for Prinsinter)

Pret: 145,29 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/panou-montaj-priza-inclinata-hypra-ip44-380-415-v-16-a-3p-n-e-plastic-231327>