



CAVI VENTILATOR TUBULATURA 100MM 300MC/H

Ventilator din plastic pentru tubulatura.

Schema de montaj si domeniul de aplicare se poate vedea in poza secundara.

Material constructiv - PP

Temperatura maxima de lucru +35 grade celsius

Alimentare la 230V/50hz

Grad de protectie IP 44

Culoare verde deschis

Sunet 60 Db

Turatie 2400 rotatii / minut

Putere electrica 70W

Flux de aer evacuat 300 mc / ora

Dimensiuni

ØA	tubulatura	Inaltime	Diametru total
----	------------	----------	----------------

WK plastics 99 Ø100	248	288
WK plastics 124 Ø125	248	288
WK plastics 149 Ø150	230	379
WK plastics 159 Ø160	230	379
WK plastics 199 Ø200	258	379
WK plastics 249 Ø250	255	379
WK plastics 315 Ø315	278	453

type	unit	WK Plastic	WK Plastic	WK Plastic	WK Plastic
		Ø100	Ø125	Ø150	Ø160
Air flow	m ³ /h	300	480	520	580
Static pressure	Pa	360	330	330	330
Static pressure	mmH ₂ O	37,72	35,17	35,17	35,17
Acoustic pressure	dB(A)	60	61	62	62
Power supply voltage	V/Hz	230/50	230/50	230/50	230/50
Motor rotation	rpm	2400	2400	2400	2400

Power	W	70	70	70	70
Current consumption	A	0,3	0,3	0,3	0,3
Max. Working Temp.	oC	35	35	35	35
Weight	kg	2,01	2,05	2,4	2,4
IP Code	IP	44	44	44	44
Insulation class					

Pret: 322,48 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ventilator-tubulatura-100mm-300mc-h>