



## **LEGRAND POWER SUPPLY MODULE CX<sup>3</sup> - 500 MA - 12 V= - 1 MODULE**

Caracteristici tehnice

Tensiune de alimentare module

500 mA 12 V = stabilized Tensiune de alimentare module for CX<sup>3</sup> energy management system

Numar de module : 1

Caracteristici generale

CX<sup>3</sup> energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX<sup>3</sup> energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>), locally ("Stand alone" ) or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 483,95 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/power-supply-module-cx3-500-ma-12-v-1-module-232253>