



LEGRAND SELF-PROTECTED DESCARCATOR SPD - PENTRU CONSUMER UNIT - T2 **- IMAX 12 KA/POLE - 1P+N LEFT**

Caracteristici tehnice

Protection for consumer units

For residential and small commercial installations

With plug-in module and status indicators:

Green: SPD operational

Red: plug-in module need to be replaced

T2 self protected SPDs - I_{max} 12 kA/pole

For installations with low risk level (in urban areas, underground Putere supplies, etc.)

In: 10 kA/pole - U_c: 275 V~

Earthing systems: TT, TNS

Cat. No. 0 039 51: SPD with Y connection (both incoming and outgoing terminals at the top of the SPD) providing better protection against overTensiunes

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1.

Numar de poli : 1P+N

Pozitie NUL : Stanga

Integrated protection : I_{sc} ? 6 kA

Numar de module : 2

Caracteristici generale

Class II (T2) low Tensiune SPDs with integrated protection

SPDs with integrated protection against overload currents and short-circuit currents

SPDs compliant with EN/IEC 61643-11 standards

For 230/400 VA Putere networks (50/60 Hz)

Pret: 507,36 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/self-protected-descarcator-spd-pentru-consumer-unit-t2->

imax-12-ka-pole-1p-n-left-233675