



## **LEGRAND SELF-PROTECTED DESCARCATOR SPD - PENTRU SECONDARY DISTRIBUTION BOARD - T2 -IMAX 12 KA/POLE -3P+N LEFT**

### Caracteristici tehnice

Protection for secondary distribution boards

Protection of sensitive equipment.

With plug-in module and status indicators:

Green: SPD operational

Red: plug-in module need to be replaced

In: 10 kA/pole - Uc: 275 V~

Earthing systems: TT, TNS.

Cat. No. 0 039 71: SPD with Y connection both incoming and outgoing terminals at the top of the SPD, providing better protection against overTensiunes

T2 self protected SPDs - I<sub>max</sub> 12 kA/pole

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1.

Numar de poli : 3P+N

Pozitie NUL : Stanga

Integrated protection : I<sub>sc</sub> ? 10 kA

Numar de module : 6

### Caracteristici generale

Class II (T2) low Tensiune SPDs with integrated protection

SPDs with integrated protection against overload currents and short-circuit currents

SPDs compliant with EN/IEC 61643-11 standards

For 230/400 VA Putere networks (50/60 Hz)

Pret: 1.387,61 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/self-protected-descarcator-spd-pentru-secondary-distribution-board-t2-imax-12-ka-pole-3p-n-left-233678>