



## **LEGRAND SIGURANTA AUTOMATA CU PROTECTIE DIFERENTIALA 6000 -10 KA - 2P-230 V~ -40 A -30 MA -AC TYPE**

### Caracteristici tehnice

2-pole - 230 V~

Compatible with prong-type supply busbars

AC Type 30 mA

C curve

Nominal rating  $I_n$  : 40 A

Numar de module : 4

### Caracteristici generale

RCBOs DX<sup>3</sup> 6000 - 10 kA - residual current circuit breakers from 3 A to 63 A - AC, A and F types

Conform to IEC 61009-1, IEC 62423 (F type)

Compatible with prong-type and fork type supply busbars

Tensiune independent tripping

Breaking capacity:

6000 - IEC 61009-1 - 10 kA / IEC 60947-2 for single pole + neutral, 2 and 4-pole

AC type : detect AC component faults

A type : detect AC and DC component faults

F type (High immunity) : detect AC and pulsating DC residual currents

Enhanced immunity to unwanted tripping in disturbed environments

Detection of high frequency fault currents

Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries and motorised controls

Pret: 424,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/siguranta-automata-cu-protectie-diferentiala-6000-10-ka-2p-230-v-40-a-30-ma-ac-type-234491>