



LEGRAND DESCARCATOR SPD - HIGH RISK LEVEL INSTALLATION. - T1+T2 - LIMP **35 KA/POLE - 440 V~(IT) -PLUG-IN -1P**

Caracteristici tehnice

SPDs for high risk level installations

SPDs for big installations with external lightning protection (LPS) and for high risk level installations according to EN/IEC 62305 standards

SPDs with plug-in module and status indicators:

Green: SPD operational

Red: plug-in module to be replaced

T1 + T2 - Iimp 35 kA/pole - 440V~ (IT) - Plug-in

Up: 2.5 kV - Uc: 440 V~

Earthing systems: TT, TNC, TNS, IT

Recommended MCCB: DPX³ 160 - 80 A

Numar de poli : 1P

Itotal (10/350) : 35 kA

Remote status monitoring (FS contact) : Yes

Numar de module : 2

Caracteristici generale

Class I + II (T1+T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz).

SPDs compliant with EN/IEC 61643-11 standards

Recommended for main distribution boards

Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes

Pret: 1.672,16 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/descarcator-spd-high-risk-level-installation-t1-t2-limp-35-ka-pole-440-v-it-plug-in-1p-235693>