



LEGRAND DESCARCATOR SPD - PROTECTION OF MAIN DISTRIBUTION BOARD - T1+T2 - LIMP 12.5 KA/POLE - 4P

Caracteristici tehnice

SPDs for general protection of main distribution board

SPDs with plug-in module and status indicators:

Green: SPD operational

Orange: plug-in module to be replaced

Earthing systems: TT, TNC, TNS

T1+T2 - Iimp 12,5 kA/pole

For general protection of big installations and protection of small installations with external lightning protection (LPS).

Up: 1.5 kV - I_{max}: 60 kA/pole - U_c: 320 V~

Recommended MCB: DX³ 63 A - C curve

Numar de poli : 4P

I_{total} (10/350) : 50 kA

Remote status monitoring (FS contact) : No

Numar de module : 4

Caracteristici generale

Class I + II (T1+T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz).

SPDs compliant with EN/IEC 61643-11 standards

Recommended for main distribution boards

Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes

Pret: 774,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/descarcator-spd-protection-of-main-distribution-board-t1-t2-limp-12-5-ka-pole-4p-235697>