



LEGRAND DESCARCATOR SPD - PROTECTION OF MAIN DISTRIBUTION BOARD - T1+T2 -LIMP 12.5 KA/POLE -3P+N LEFT

Caracteristici tehnice

SPDs for general protection of main distribution board

SPDs with plug-in module and status indicators:

Green: SPD operational

Orange: plug-in module to be replaced

Earthing systems: TT, TNC, TNS

T1+T2 - I_{imp} 12,5 kA/pole

For general protection of big installations and protection of small installations with external lightning protection (LPS).

Up: 1.5 kV - I_{max}: 60 kA/pole - U_c: 320 V~

Recommended MCB: DX³ 63 A - C curve

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1

Numar de poli : 3P+N

Pozitie NUL : Stanga

I_{total} (10/350) : 50 kA

Remote status monitoring (FS contact) : Yes

Numar de module : 4

Caracteristici generale

Class I + II (T1+T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz).

SPDs compliant with EN/IEC 61643-11 standards

Recommended for main distribution boards

Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes

Pret: 865,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/descarcator-spd-protection-of-main-distribution-board-t1-t2-limp-12-5-ka-pole-3p-n-left-235707>