



## **LEGRAND DESCARCATOR SPD - T2 - IMAX 20 KA/POLE - 3P+N - NUL IN DREAPTA**

Caracteristici tehnice

T2 SPDs

SPDs with plug-in module and status indicators:

Green: SPD operational

Orange: plug-in module to be replaced

T2 - I<sub>max</sub> 20 kA/pole

SPDs recommended for small installations

Up: 1.2 kV - I<sub>n</sub>: 5 kA/pole - U<sub>c</sub>: 320 V~

Earthing systems : TT, TNC, TNS

Recommended MCB: DX<sup>3</sup> 20 A - C curve

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1

Numar de poli : 3P+N

Pozitie NUL : Dreapta

Remote status monitoring (FS contact) : No

Numar de module : 4

Caracteristici generale

Class II (T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz). SPDs compliant with EN/IEC 61643-11 standards

Recommended for distribution boards

Pret: 408,41 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/descarcator-spd-t2-imax-20-ka-pole-3p-n-nul-in-dreapta-235711>