



## **LEGRAND DESCARCATOR SPD - T2 - IMAX 40 KA/POLE - 3P+N - NEUTRAL ON PE** **PARTEA DREAPTA**

### Caracteristici tehnice

#### T2 SPDs

SPDs with plug-in module and status indicators:

Green: SPD operational

Orange: plug-in module to be replaced

T2 - I<sub>max</sub> 40 kA/pole

SPDs recommended for Putere installations

Up: 1.7 kV - I<sub>n</sub>: 20 kA/pole - U<sub>c</sub>: 320 V~

Earthing systems : TT, TNC, TNS

Recommended MCB: DX<sup>3</sup> 25 A - C curve

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1

Numar de poli : 3P+N

Pozitie NUL : Dreapta

Remote status monitoring (FS contact) : No

Numar de module : 4

### Caracteristici generale

Class II (T2) low Tensiune SPDs

Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz). SPDs compliant with EN/IEC 61643-11 standards

Recommended for distribution boards

Pret: 520,67 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/descarcator-spd-t2-imax-40-ka-pole-3p-n-neutral-on-pe-partea-dreapta-235718>