



## **LEGRAND STANDARD LED LAMPA DE EMERGENTA TWINSPOUT - NON AUTOTEST - 2 X 1250 LM - 1H**

Caracteristici tehnice

Standard LED spotlight luminaires - Non-Maintained (NM)

2 x 1250 lm – 1h

Caracteristici generale

LED Twinspot emergency lighting luminaires

High performance LED non maintained emergency lighting luminaires

Certified to IEC and EN 60598-2-22 standards

High Putere LEDs spotlights with optimized lighting distribution

Low Consum electronic switching Tensiune de alimentare

High capacity terminals: 2 x 2.5 mm<sup>2</sup> - IP 55 - IK 07

Duration: 1, 2 and 3 hours. Ni-Cd batteries. Recharge time: 24h

Green charge indicator with high luminosity LED, to improve visibility from the floor when high installation

Tensiune de alimentare: 230 V~ ± 10% - 50/60 Hz. Class II

Rest mode with remote control device Cat.No 0 039 01 to avoid battery discharge in case of voluntary Putere cut

Surface mounting installation with 4 wall-mounting lugs (Cat.No 0 358 02, supplied) or 4 screws (not supplied)

Pret: 3.897,26 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/standard-led-lampa-de-emergenta-twinspot-non-autotest-2-x-1250-lm-1h-235820>