



## **LEGRAND STATE REPORTING MODULE CX<sup>3</sup> - UNIVERSAL SIGNALLING - 3 LED LIGHTS - 1 MODULE**

Caracteristici tehnice

State reporting module

Universal signalling module

Enables upstream busbar connection

Equipped with 3 LED lights: green, red and yellow

Indicates various type of information, according to selected configuration:

contacts position, plugged-in or drawn-out product, etc...

Equipped with DIP switches (on the side) allowing product configuration: selection of information type and of the LED behaviour

Compatible with symmetrical rail mounting protection devices or head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>)

Consum: 0.377 W - 31.4 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX<sup>3</sup> energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX<sup>3</sup> energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>), locally ("Stand alone" ) or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 513,40 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/state-reporting-module-cx3-universal-signalling-3-led-lights-1-module-235847>