



## **LEGRAND SURSA STABILIZATA -SINGLE/TWO-PINALTIME -120-480 W -OUTPUT 24 V= -480 W**

### Caracteristici tehnice

Single/two-phase 120 - 480 W wide input Tensiune range  
Suitable for single or two-phase networks  
Also suitable for three-phase networks, when using 2 phases only  
Low harmonic pollution due to the integrated PFC filter (from 240 W)  
Adjustable output Tensiune  
Aluminium casing  
Input Tensiune: 200 to 500 V~ Output Tensiune: 24 V=  
Nominal Putere : 480 W  
Nominal rating : 20 A  
Setting range : 24 to 28 V  
Width : 86 mm

### Caracteristici generale

Stabilised switched mode Putere supplies - single/two-phase and three-phase  
Conforming to standards UL 508, IEC EN 60950-1 and IEC EN 61204-3  
UL-approved in USA (and Canada for Cat. Nos. 1 466 54/63/82)  
Operating frequency: 50/60 Hz  
Output Tensiune present indicator  
Potentiometer for adjusting the output Tensiune on front panel  
Integrated short-circuit and overload protection  
With signal or relay contact for feedback on the status of the active output Tensiune  
Connection with copper conductors only  
For mounting on a symmetrical rail depth 7.5 mm and 15 mm  
Pret: 3.115,13 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/sursa-stabilizata-single-two-pinaltime-120-480-w-output->

