



LEGRAND TRANSFORMATOR DE SIGURANTA - 230-400 V / 24-48 V - 100 VA - 2 X 4 MM²

Caracteristici tehnice

Safety transformers

Conform to standard IEC EN 61558-2-6

For 63 VA transformers:

Fuse cartridges: 5 x 20 time-delayed

Fuse carrier: Cat.No 0 371 81

For 100 VA and greater transformers:

Up to 25 A : gG 10 x 38 fuse cartridges and fuse carrier Cat. No. 0 058 08

From 25 A to 50 A : gG 14 x 51 fuse cartridges and fuse carrier Cat.No 0 215 01

From 50 A upwards : gG 22 x 58 fuse cartridges and fuse carrier Cat.No 0 216 01

C curve MCBs

Input Tensiune = 230-400 V~ Output Tensiune = 24-48 V~

Putere : 100 VA

Primary terminal flexible cable : 4 mm²

Secondary terminal flexible cable cross-section : 4 mm²

Caracteristici generale

Transformers and auto-transformers IP 55 - class II - single-phase

Pret: 1.454,73 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/transformator-de-siguranta-230-400-v-24-48-v-100-va-2-x-4-mm2-236784>