



LEGRAND UNIVERSAL CONTROL MODULE CX³ - 2 RELAYS 240 V~ - 6 A - 1 MODULE

Caracteristici tehnice

Universal control module

Enables upstream busbar connection

2 relays: 240 V~ - 6 A

Enables to remotely control different electrical loads or motorised controls associated to symmetrical rail mounting protection devices or head equipment (DPX³ MCCBs)

Equipped with DIP switches (on the side) allowing product configuration: contact type (NO + NC, 2 NO, etc...) and function (maintained or momentary contact)

Consum: 0.456 W - 38 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 570,07 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/universal-control-module-cx3-2-relays-240-v-6-a-1-module-237077>