





LEGRAND UNIVERSAL VARIATOR MOSAIC - CUOUT NEUTRAL - ALU - 2 MODULE

Caracteristici tehnice Dimmer switches 110-230 V~- 50 Hz Can be remotely controlled via non-illuminated pushbuttons, with each pushbutton able to perform the dimming function When switched on, lighten at the level set before last switched off For installation in Montaj incastrat box depth 40 mm min Universal dimmer without neutral, 2-wire For all types of lamps: dimmable LEDs: 5 W to 75 W (10 lamps max.) dimmable compact fluorescent lamps: 5 W to 75 W (10 lamps max.) halogen with ferromagnetic or electronic transformer: 3 VA to 400 VA fluorescent tube - ballast: 3 VA to 200 VA halogen and incandescent 230 V: 3 W to 400 W When switched on, gradually (2 seconds) lights up at the level set before last switch-off Functionning: dimming mode pre-set level mode (0%, 33%, 66%, 100%) nightlight mode: dimming down of the lamp for 1 hour 2 module Alu Caracteristici generale Mosaic[™] Programme mechanisms - dimming control Pret: 356,70 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/universal-variator-mosaic-cuout-neutral-alu-2-module-237081